


Universe	Professional
Type	Verticality
Category	Anchors
Subcategory	Rock and concrete anchors




COEUR BOLT STEEL

The COEUR BOLT STEEL is a standard steel anchor made up of a COEUR STEEL hanger, a bolt, and a nut. It is designed for interior use or non-permanent installations. It is available in 10 and 12 mm diameters.



Featuring a large attachment point, Petzl hangers are easy to clip into and can accommodate two carabiners, even thick ones, in the same anchor.



Petzl hangers are characterized by high thickness and rounded edges on the attachment points. This construction minimizes wear on connectors, regardless of their material composition.



Petzl hangers are textured on the back side that is in contact with the structure (concrete, rock, or other). This helps prevent the hanger from turning when the anchor is being installed or when it is heavily laterally loaded during use.

Short Description Standard steel anchor for interior use or non-permanent installations (pack of 20)

Selling Points

- Economical choice for low-corrosion environments
- Assembly composed of a COEUR STEEL hanger, a bolt, and a nut
- Easy to clip:
 - the wide, ergonomic connection point facilitates carabiner clipping
 - the width of the attachment point allows installation of two carabiners at the same time
- Reduces wear on connectors: the thickness of the hanger and the rounded edges of the connection point minimize wear on connectors
- Hanger anti-rotation system: textured back keeps the hanger from turning when the anchor is being installed or when it is heavily laterally loaded during use
- Available in two bolt sizes (10 or 12 mm)
- COEUR STEEL hangers, available separately:
 - for 10 mm diameter bolt (P36AA 10)
 - for 12 mm diameter bolt (P36AA 12)

Specification

- Material(s): steel
- Certification(s): EN 959, GB 30862/A

Specifications by reference

Reference(s)	P36BA 10	P36BA 12
		
Diameter	10 mm	12 mm
Weight	110 g	135 g
Drilling diameter	10 mm	12 mm
Total bolt length	85 mm	105 mm
Shear strength in 50 MPa concrete	23 kN	25 kN
Pull-out strength in concrete 50 MPa	15 kN	18 kN
Made in	FR	FR
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	1	1
EAN	3342540104198	3342540104136

Spare part(s) COEUR STEEL
BOLT STEEL